

E-Revo® VXL Brushless (Model 86086-4) Parts List

Parts show	n in bold are optional accessories. Part categories and individual part listings a	re arranged	alphabetically.
	Bearings & Bushings	5628	Vent, battery compartment (includes latch) (1 pair, fits left or right side)
5107A	Ball bearing, black rubber sealed (17x26x5mm)(2)	4074	•
5120	Ball bearings, blue rubber sealed (12x18x4mm) (2)	4974 5473	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4) Wheelie bar mount (1)(fits 1/10 scale Revo trucks)
5101	Ball bearings, blue rubber sealed (12x21x5mm) (2)	5473	Wheelie bar, assembled (fits all 1/10th scale Revo trucks)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	4976	Wheels (4)/ axles (2) (for T-Maxx®/E-Maxx wheelie bar)
5114	Ball bearings, blue rubber sealed (5x8x2.5mm) (2)		Cush Drive Components
5180	Ball bearings, blue rubber sealed (6x13x5mm) (2)		<u>-</u>
5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)	6465	Cush drive key / pin/ elastomer damper
	Body & Accessories	6487X 7793X	Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
1926	Antenna caps, vinyl (2)/ antenna spool	6447	Housing, cush drive (front & rear halves) Spur gear, 46-tooth (1.0 metric pitch)
5526	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tools	6447R	Spur gear, 46-tooth (1.0 metric pitch) Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)
5526R	Antenna crimp nut, aluminum (red-anodized)/ antenna nut tools	6448	Spur gear, 50-tooth (1.0 metric pitch)
1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	6448R	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch)
8615	Body mounts, front & rear/ 3x12mm CS (4)/ 3x12mm shoulder screw	6449	Spur gear, 54-tooth (1.0 metric pitch)
0614	(2)/ 3x10mm flat-head machine screw (8)/ 3x12mm BCS (1)	6449R	Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)
8614	Body posts, clipless, front & rear (1 each)		Differential Components
8610 8613	Body reinforcement set (fits #8611 body) Body support/ 3x12mm CS (4)	5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)
8611R	Body, E-Revo, black/ window, grille, lights decal sheet	8681X	Carrier, differential (aluminum)/ x-ring gaskets (2)/ ring gear gasket/
001110	(assembled with front & rear body mounts and rear body support	000170	spacers (4)/ 12.2x18x0.5 metal washer
	for clipless mounting)	8681	Carrier, differential (heav y duty)/ x-ring gaskets (2)/ ring gear gasket/
8611X	Body, E-Revo, blue/ window, grille, lights decal sheet (assembled		spacers (4)/ 12.2x18x0.5 PTFE-coated washer (1)
	with front & rear body mounts and rear body support for clipless	8687	Center differential, complete (fits E-Revo® VXL)
06117	mounting)	8680	Differential gasket/ x-rings (2)/ 12.2x18x0.5 metal washer (1)/
8611T	Body, E-Revo, purple/ window, grille, lights decal sheet (assembled with front & rear body mounts and rear body support for clipless	F400**	12.2x18x0.5 PTFE-coated washer (1)
	mounting)	5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
8611	Body, E-Revo® (clear, requires painting)/ window, grille, lights	8686 8682	Differential, front or rear, complete (fits E-Revo® VXL) Gear set, differential (spider gears (4), spider gear shaft (2))
	decal sheet	5130	Oil, differential (100K wt) (0.7 oz (20cc))
2514	Decal sheet, racing sponsors	5135	Oil, differential (10K wt)
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)	5040	Oil, differential (20M wt) (standard)
8617	Skid plate, roof (body)/ 3x12mm CS (4)	5136	Oil, differential (30K wt)
5185	Tires, rubber (2) (fits Traxxas® wheelie bar wheels)	5137	Oil, differential (50K wt)
4974	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)	8684	Output gear, center differential, hardened steel (2)
5473	Wheelie bar mount (1)(fits 1/10 scale Revo trucks)	8683	Output gears, differential, hardened steel (2)
5472 4976	Wheelie bar, assembled (fits all 1/10th scale Revo trucks) Wheels (4)/ Axles (2), for wheelie bar	8679	Ring gear, differential/ pinion gear, differential
5413	Wing mount, center / wing washers (for Revo®)		Driveline Components
8616	Wing mounts, low profile	8635	Axle carriers, left & right (1 each) (use with 8x16mm & 17x26mm ball
5446	Wing, Revo® (black)/ decal sheet		bearings)/ dust boot retainers (4)
5446G	Wing, Revo® (Exo-Carbon finish)/ decal sheet	8652	Drive cup, machined steel (2)/ 4x17mm screw pins (2)
5412	Wing, Revo® (white)/ decal sheet	8650	Driv eshaft, steel constant-v elocity (heavy duty, shaft only, 122.5mm)
	Bumpers & Skidplates	8655R	Driveshafts, center E-Revo® (steel constant-velocity) front (1)/
5335X	Bumpers, front and rear (black chrome)	5150	rear (1) (assembled with inner and outer dust boots, for E-Revo) E-clips, 1.5mm (24)
5315	Guards, steering serv o (2)	8655	Half shafts, center (internal splined (2)/ external splined (2)) (plastic
8637	Skid plate set, front/ skid plate, rear/ 3x10 BCS (6)/ 3x30 BCS (1) (fits	0000	parts only)
	#8629 & 8630 bulkheads)	8651	Rebuild kit, driv eshaft (cross pin (2)/ 16mm pin (2)) (metal parts for 2
5637X	Skidplate, transmission, ny lon (black)/ cov er		driv eshafts)
	Chassis & Attachments	5145	Screw pin, 4x15mm (6)
8615	Body mounts, front & rear/ 3x12mm CS (4)/ 3x12mm shoulder screw	8653	Stub axle
· · · · -	(2)/ 3x10mm flat-head machine screw (8)/ 3x12mm BCS (1)	5452	U-joints, driv eshaft (carrier (4)/ 4.5mm cross pin (4)/ 3mm cross pin
5624	Box, receiver (sealed)/ foam pad/ silicone grease/ 3x8mm BCS (2)/	8654	(4)/ e-clips (20)) (metal parts for 2 driveshafts) Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4)/ 3x14mm
=0.5 -	2.5x8mm CS (2)/ 3x6mm BCS (2)	0004	pin (4)
5323	Bulkhead tie bars, front & rear (blue-anodized aluminum)	8654G	Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4)/
5323R	Bulkhead tie bars, front & rear (red-anodized aluminum)		3x14mm pin (4)
8630	Bulkhead, front (upper and lower)/ 4x12mm BCS (6) (requires #8622 chassis)	8654A	Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4)/
8629	Bulkhead, rear (upper and lower)/ 4x12mm BCS (6) (requires #8622		3x14mm pin (4)
5025	chassis)	8654R	Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4)/
8620	Chassis supports, front & rear/ 3x12mm BCS (4)/ 3x15mm CS (4)/	77504	3x14mm pin (4)
	4x14mm BCS (1)	7758A	Wheel nuts, splined, 17mm, serrated (black-anodized) (4)
8622	Chassis, E-Revo® (requires #8629 & 8630 bulkheads)	7758 7758G	Wheel nuts, splined, 17mm, serrated (blue-anodized) (4) Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
5627	Door, battery compartment (2) (fits right or left side)	7758T	Wheel nuts, splined, 17mm, serrated (green-anodized) (4) Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)
5315	Guards, steering servo (2)	7758R	Wheel nuts, splined, 17mm, serrated (trange-anodized) (4)
5629	Retainer clip, battery (1)/ front clip (1) /rear clip (1)/ foam spacer (1)	8658	Yokes, transmission (2)/ 4x15mm screw pins (2)
562F	(for one battery compartment)		Front Suspension
5625 5317	Seal kit, receiv er box (includes o-ring, seals, and silicone grease) Shock mounts (front & rear)/ wire clip (1)/ chassis wire clips (4)/	0625	
5011	3x32mm CS (4)/ 3x6mm BCS (1)	8635	Axle carriers, left & right (1 each) (use with 8x16mm & 17x26mm ball bearings)/ dust boot retainers (4)
8637	Skid plate set, front/ skid plate, rear/ 3x10 BCS (6)/ 3x30 BCS (1) (fits	5323	Bulkhead tie bars, front & rear (blue-anodized aluminum)
	#8629 & 8630 bulkheads)	5323R	Bulkhead tie bars, front & rear (red-anodized aluminum)
5637X	Skidplate, transmission, ny lon (black)/ cov er	8630	Bulkhead, front (upper and lower)/ 4x12mm BCS (6) (requires #8622
5185	Tires, rubber (2) (fits Traxxas® wheelie bar wheels)		chassis)

Page 2			,	
5134	Caster spacers (4)/ shims (4)	3936	Screws, 4x10mm button-head machine (hex drive) (6)	
5378X	Piv ot ball caps (4)/ dust boots, rubber (4)/ dust plugs, rubber (4)/ dust boot retainers, black (4), blue (4) (2 pkgs. req. to complete truck)	3937 3938	Screws, 4x12mm button-head machine (hex drive) (6) Screws, 4x14mm button-head machine (hex drive) (6)	
4933	Piv ot balls (4)/ piv ot ball cap bushings (4)	3929	Screws, 4x18mm button-head machine (hex driv e) (6)	
4933X	Pivot balls, hard-anodized 7075-T6 aluminum (4)/ pivot ball cap	3939	Screws, 4x6mm button-head machine (hex drive) (with threadlock) (6)	
8619	bushings (4) Push rods (steel), heavy duty (2) (assembled with rod ends)	4897	Screws, set (grub) 4mm (6) (with threadlock)	
8619X	Push rods, aluminum (blue-anodized), heavy duty (2) (assembled		Motors & Electronics	
	with rod ends and threaded inserts)	3475	Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)	
8619G	Push rods, aluminum (green-anodized), heavy duty (2)	2072A 2252	Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos)	
8619R	(assembled with rod ends and threaded inserts) Push rods, aluminum (red-anodized), heavy duty (2) (assembled	2072R	Gear set, metal, high speed (for 2070, 2075 servos)	
001010	with rod ends and threaded inserts)	8661	Motor mount hinge post/fixed gear adapter/ 5x25mm BCS (1)/	
5354X	Rocker arm post (aluminum) (4)	F660	4x16mm CS with split and flat washer (1)	
5354 5358	Rocker arm post (steel) (2) Rocker arm set, progressive-2 (90-T)/ spacers (red aluminum) (8)	5660 3481	Motor mount, finned aluminum Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors	
8647X	Rod ends, heavy duty (push rod) (8) (assembled with hollow balls)		& high-efficiency heatsink)	
	(replacement ends for #8619, 8619G, 8619R, 8619X)	8690	Plate, motor	
8646	Rod ends, heavy duty (toe links) (8) (assembled with hollow balls)	2254	Servo case, aluminum (blue-anodized) (middle) (for 2250 servo)	
8632X	Suspension arms, blue, front (left), heavy duty (upper (1)/ lower (1))	2253 2251	Servo case, aluminum (red-anodized) (middle) (for 2255 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for	
8631X	Suspension arms, blue, front (right), heavy duty (upper (1)/ lower	220.	2250, 2255 servos)	
	(1))	2074	Serv o case/gaskets (for 2056 and 2075 waterproof serv os)	
8632 8631	Suspension arms, front (left), heavy duty (upper (1)/ lower (1)) Suspension arms, front (right), heavy duty (upper (1)/ lower (1))	2075R 2075	Servo, digital high-speed, metal gear (ball bearing), waterproof	
8632G	Suspension arms, green, front (left), heavy duty (upper (1)/ lower	2075 2250	Serv o, digital high-torque (ball bearing), waterproof Servo, digital high-torque 330 coreless, metal gear (ball bearing)	
	(1))		waterproof	
8631G	Suspension arms, green, front (right), heavy duty (upper (1)/	2255	Servo, digital high-torque 400 brushless, metal gear (ball	
8632T	lower (1)) Suspension arms, orange, front (left), heavy duty (upper (1)/	2075X	bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof	
00021	lower (1))	3480	Velineon® VXL-6s Brushless Power System, waterproof (includes	
8631T	Suspension arms, orange, front (right), heavy duty (upper (1)/		VXL-6s ESC and 2200Kv, 75mm motor)	
8632R	lower (1)) Suspension arms, red, front (left), heavy duty (upper (1)/ lower	3485	Velineon® VXL-6s Electronic Speed Control, waterproof (brushless) (f wd/rev/brake)	
003210	(1))			
8631R	Suspension arms, red, front (right), heavy duty (upper (1)/ lower	2872X	Radio System, Batteries & Chargers 5000mAh 11.1v 3-Cell 25C LiPo Battery	
8632A	(1)) Suspension arms, white, front (left), heavy duty (upper (1)/ lower	2842X	5000mAh 7.4v 2-Cell 25C LiPo Battery	
003ZA	(1))	2843X	5800mAh 7.4v 2-Cell 25C LiPo Battery	
8631A	Suspension arms, white, front (right), heavy duty (upper (1)/	2869X	7600mAh 7.4v 2-Cell 25C LiPo Battery	
5321	lower (1)) Suspension pin set (front or rear, hardened steel), 3x20mm (4),	2938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries to separate balance ports)	
3321	3x40mm (2))	5526	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tools	
8638	Toe link, 5.0mm steel (front or rear) (2)	5526R	• • • • • • • • • • • • • • • • • • • •	
8638X	Toe links, E-Revo® VXL (TUBES blue-anodized, 7075-T6	1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	
	aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm	2943 6548	Battery charge indicators (green (4), blue (4), gray (4)) Battery door, transmitter (replacement for #6516, 6517, 6528, 6529,	
	(1)		6530 transmitters)	
8638G	Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6	2914	Battery, Power Cell AA Alkaline (4)	
	aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm	2991	Battery/charger completer pack (includes #2972 Dual iD® charger (1), #2869X 7600mAh 7.4V 2-cell 25C LiPo battery (2))	
	(1)	2990	Battery/charger completer pack (includes #2972 Dual iD®	
8638R	Toe links, E-Revo® VXL (TUBES red-anodized, 7075-T6		charger (1), #2872X 5000mAh 11.1V 3-cell 25C LiPo battery (2))	
	aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm	2972	Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery	
	(1)	2973	Identification Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto	
	Hardware		Battery Identification	
5150	E-clips, 1.5mm (24)	2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery	
5477	Flat wrench, 5mm (blue-anodized aluminum)	2981	Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto	
5478 3090	Flat wrench, 8mm (blue-anodized aluminum)		Battery Identification	
3980 2586	Glow plug wrench (universal wrench) Head screws, 3x15mm cap-head machine (hex drive) (6) (TRX 2.5)	2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto	
5476X	Hex wrenches; 1.5mm, 2mm, 2.5mm, 3mm, 2.5mm ball	5632	Battery Identification Chassis brace, rear (fits E-Revo®/Summit)	
5475	Multi-tool (plastic)	6525	Communication link, telemetry expander	
5144 5145	Screw pin, 2.5x18mm (6) Screw pin, 4x15mm (6)	6566	Data Link cable, telemetry expander (connects #6550X telemetry	
3236	Screws, 2.5x12mm cap-head machine (6)		expander 2.0 to the #3485 VXL-6s or #3496 VXL-8s electronic	
3965	Screws, 2.5x8mm cap-head machine (6)	2072A	speed control) Gear set (for 2070, 2075 servos)	
2577	Screws, 3x10mm button-head machine (hex drive) (6)	2252	Gear set, metal (for 2250, 2255 servos)	
	Screws, 3x10mm cap-head machine (6) (no washer) Screws, 3x10mm countersunk machine (6) (hex driv e)	2072R	Gear set, metal, high speed (for 2070, 2075 servos)	
		2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)	
2551 5282	Screws, 3x12mm button-head machine (6) (starter attachment screws		LiPo cell voltage checker/balancer (requires #2938X adapter for	
2551 5282	with threadlock)	2968	LIFO CEIL VOILAGE CHECKEL/DAIAHCEL HEUUH ES #2330X AUADLEL IOI	
5282 2578	with threadlock) Screws, 3x12mm button-head machine (hex drive) (6)		Traxxas® iD® batteries)	
2551 5282 2578 2552	with threadlock) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x12mm countersunk machine (6) (hex drive)	2968 6556	Traxxas® iD® batteries) Mount, telemetry expander (fits XO-1®, E-Revo®*, Summit*, all T-	
2551 5282 2578	with threadlock) Screws, 3x12mm button-head machine (hex drive) (6)		Traxxas® iD® batteries) Mount, telemetry expander (fits XO-1®, E-Revo®*, Summit*, all T- Maxx®/E-Maxx® trucks, Revo® 3.3, Slayer Pro 4X4) (*requires	
2551 5282 2578 2552 2579 2553 2581	with threadlock) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x12mm countersunk machine (6) (hex drive) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x25mm button-head machine (hex drive) (6)		Traxxas® iD® batteries) Mount, telemetry expander (fits XO-1®, E-Revo®*, Summit*, all T-	
2551 5282 2578 2552 2579 2553	with threadlock) Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x12mm countersunk machine (6) (hex drive) Screws, 3x15mm button-head machine (hex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive)	6556	Traxxas® iD® batteries) Mount, telemetry expander (fits XO-1®, E-Revo®*, Summit*, all T- Maxx®/E-Maxx® trucks, Revo® 3.3, Slayer Pro 4X4) (*requires rear chassis brace #5632)	

6552

grease)

2575

2576

Screws, 3x6mm button-head machine (hex drive) (6)

Screws, 3x8mm button-head machine (hex drive) (6)

Seal kit, expander box (includes o-ring, seals, and silicone

Page 3	E-Revo® VXL Brushless: TQi™ Traxxas Link™ Ena	bled 2.4	GHz Radio & TSM® (Model 86086-4) Parts List
6526	Sensor, auto-detectable, temperature	8634A	Suspension arms, white, rear (left), heavy duty, adjustable
6527	Sensor, auto-detectable, voltage	06224	wheelbase (upper (1)/ lower (1))
6521	Sensor, temperature and voltage (long)	8633A	Suspension arms, white, rear (right), heavy duty, adjustable wheelbase (upper (1)/ lower (1))
2254 2253	Servo case, aluminum (blue-anodized) (middle) (for 2250 servo) Servo case, aluminum (red-anodized) (middle) (for 2255 servo)	5321	Suspension pin set (front or rear, hardened steel), 3x20mm (4),
2251	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for		3x40mm (2))
	2250, 2255 servos)	8638	Toe link, 5.0mm steel (front or rear) (2)
2074	Serv o case/gaskets (for 2056 and 2075 waterproof serv os)	8638X	Toe links, E-Revo® VXL (TUBES blue-anodized, 7075-T6
2075R	Servo, digital high-speed, metal gear (ball bearing), waterproof		aluminum, stronger than titanium) (144mm) (2)/ rod ends,
2075	Serv o, digital high-torque (ball bearing), waterproof		assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1)
2250	Servo, digital high-torque 330 coreless, metal gear (ball bearing),	8638G	Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6
2255	waterproof	00000	aluminum, stronger than titanium) (144mm) (2)/ rod ends,
2255	Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof		assembled with steel hollow balls (8)/ aluminum wrench, 10mm
2075X	Servo, digital high-torque, metal gear (ball bearing), waterproof		(1)
6553X	Telemetry expander 2.0 and GPS module 2.0, TQi radio system	8638R	Toe links, E-Revo® VXL (TUBES red-anodized, 7075-T6
6550X	Telemetry expander 2.0, TQi radio system (for use only with		aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm
	#6551X GPS module)		(1)
6551X	Telemetry GPS module 2.0, TQi radio system (for use only with		Shock Oil
6509R	#6550X telemetry expander) TQi 2.4 GHz High Output radio system, 2-channel, Traxxas Link™	5004	
0309K	enabled, TSM (2-ch transmitter, 5-ch micro receiver)	5031 5032	Oil, shock (20 wt, 200 cSt, 60cc) (silicone)
6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas	5032	Oil, shock (30 wt, 350 cSt, 60cc) (silicone) Oil, shock (40 wt, 500 cSt, 60cc) (silicone)
	Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro	5034	Oil, shock (50 wt, 600 cSt, 60cc) (silicone)
	receiver)	5035	Oil, shock (60 wt, 700 cSt, 60cc) (silicone)
6528	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-	5036	Oil, shock (70 wt, 900 cSt, 60cc) (silicone)
	channel (transmitter only)	5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)
6529	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-	5029	Shock oil bottle (60cc) (for mixing shock oil)
6530	channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-	5038X	Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, &
0330	channel (transmitter only)	4007	80 wt premium shock oils with spinning carousel rack)
6511	Traxxas Link™ Wireless Module	1667	Silicone shock oil (30 wt), 60cc
	Ready-To-Race Model	5038	Spinning carousel rack
86086-4	E-Rev o® VXL Brushless: 1/10 Scale 4WD Brushless Electric		Shocks (GTR)
00000-4	Monster Truck with TQi™ 2.4GHz Traxxas Link™ Enabled Radio	5466X	Body, GTR shock (hard-anodized, PTFE-coated aluminum) (1)
	System and Traxxas Stability Management (TSM)®	5465	Caps and spring retainers, GTR shock (upper cap (2)/ hollow balls
	Rear Suspension	5475	(2)/ bottom cap (2)/ upper retainer (2)/ lower retainer (2)) Multi-tool (plastic)
8635	Axle carriers, left & right (1 each) (use with 8x16mm & 17x26mm ball	5158	Nuts, 2.5mm ny lon locking (12)
8033	bearings)/ dust boot retainers (4)	5462	Rebuild kit, GTR shock (x-rings, bump stops, bladders, all pistons,
5323	Bulkhead tie bars, front & rear (blue-anodized aluminum)		piston nuts, shock rod ends) renews 2 shocks
5323R	Bulkhead tie bars, front & rear (red-anodized aluminum)	5469	Rod ends (GTR shocks) (6)
8629	Bulkhead, rear (upper and lower)/ 4x12mm BCS (6) (requires #8622	5463	Shaft, GTR shock (2) (stainless)
	chassis)	5463T	Shaft, GTR shock, TiN-coated (2)
5378X	Piv ot ball caps (4)/ dust boots, rubber (4)/ dust plugs, rubber (4)/ dust	5460	Shocks, GTR aluminum (assembled) (2) (without springs)
4933	boot retainers, black (4), blue (4) (2 pkgs. req. to complete truck) Piv ot balls (4)/ piv ot ball cap bushings (4)	5460A	Shocks, GTR aluminum, blue-anodized (fully assembled w/o
4933X	Pivot balls, hard-anodized 7075-T6 aluminum (4)/ pivot ball cap	5460R	springs) (4) Shocks, GTR aluminum, red-anodized (fully assembled w/o
4000%	bushings (4)	0-10011	springs) (4)
8619	Push rods (steel), heavy duty (2) (assembled with rod ends)	5460X	Shocks, GTR hard-anodized, PTFE-coated aluminum bodies with
8619X	Push rods, aluminum (blue-anodized), heavy duty (2) (assembled		TiN shafts (fully assembled w/o springs) (4)
	with rod ends and threaded inserts)	5461	Variable damping kit, GTR shocks (includes #1, #2, #3 pistons
8619G	Push rods, aluminum (green-anodized), heavy duty (2)		and stainless steel valves)
8619R	(assembled with rod ends and threaded inserts) Push rods, aluminum (red-anodized), heavy duty (2) (assembled		Springs
001011	with rod ends and threaded inserts)	5435	Spring, shock (red) (GTR) (2.6 rate yellow) (1 pair)
5354X	Rocker arm post (aluminum) (4)	5436	Spring, shock (red) (GTR) (2.9 rate white) (1 pair)
5354	Rocker arm post (steel) (2)	5437	Spring, shock (red) (GTR) (3.2 rate orange) (1 pair)
5358	Rocker arm set, progressiv e-2 (90-T)/ spacers (red aluminum) (8)	5438	Spring, shock (red) (GTR) (3.5 rate green) (1 pair) Spring, shock (red) (GTR) (3.8 rate gold) (1 pair)
8647X	Rod ends, heavy duty (push rod) (8) (assembled with hollow balls)	5439 5440	Spring, shock (red) (GTR) (4.1 rate tan) (1 pair)
0646	(replacement ends for #8619, 8619G, 8619R, 8619X)	5441	Spring, shock (red) (GTR) (4.4 rate black) (1 pair)
8646 8634X	Rod ends, heavy duty (toe links) (8) (assembled with hollow balls) Suspension arms, blue, rear (left), heavy duty, adjustable	5442	Spring, shock (red) (GTR) (4.9 rate silver) (std. front 120mm) (1
0034A	wheelbase (upper (1)/ lower (1))	· · · -	pair)
8633X	Suspension arms, blue, rear (right), heavy duty, adjustable	5444	Spring, shock (red) (GTR) (5.9 rate blue) (std. rear 120mm) (1
	wheelbase (upper (1)/ lower (1))		pair)
8634G	Suspension arms, green, rear (left), heavy duty, adjustable	5445	Spring, shock (red) (GTR) (6.4 rate purple) (1 pair)
	wheelbase (upper (1)/ lower (1))	5443	Spring, shock red (GTR) (5.4 rate pink) (1 pair)
8633G	Suspension arms, green, rear (right), heavy duty, adjustable		Spur Gears & Pinion Gears
8634T	wheelbase (upper (1)/ lower (1)) Suspension arms, orange, rear (left), heavy duty, adjustable	6484X	Gear, 11-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
00341	wheelbase (upper (1)/ lower (1))		(for use only with steel spur gears)
8633T	Suspension arms, orange, rear (right), heavy duty, adjustable	6485X	Gear, 12-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	wheelbase (upper (1)/ lower (1))	EAGEV	(for use only with steel spur gears)
8634	Suspension arms, rear (left), heavy duty, adjustable wheelbase	6486X	Gear, 13-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw (for use only with steel spur gears)
0000	(upper (1)/ lower (1))	6488X	Gear, 14-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
8633	Suspension arms, rear (right), heavy duty, adjustable wheelbase	6487X	Gear, 15-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
8634R	(upper (1)/ lower (1)) Suspension arms, red, rear (left), heavy duty, adjustable	6489X	Gear, 16-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
000711	wheelbase (upper (1)/ lower (1))	6490X	Gear, 17-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
8633R	Suspension arms, red, rear (right), heavy duty, adjustable	6491X	Gear, 18-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw
	wheelbase (upper (1)/ lower (1))	6491R	Gear, 18-T pinion (machined) (1.0 metric pitch) (fits 5mm shaft)/
			set screw

Page 4	E-Revo® VXL Brushless:	TQi™ Traxxas Link¹	M Enabled 2.4GHz Radio	& TSM®	(Model 86086-4) Parts List
--------	------------------------	--------------------	------------------------	--------	----------------	--------------

6494X 6447	Gear, 20-T pinion (1.0 metric pitch) (fits 5mm shaft)/ set screw Spur gear, 46-tooth (1.0 metric pitch)		Tires & Wheels
6447R	Spur gear, 46-tooth (1.0 metric pitch) Spur gear, 46-tooth, steel (wide-face, 1.0 metric pitch)	8674	Tires & wheels, assembled, glued (black 3.8" wheels, paddle
448	Spur gear, 50-tooth (1.0 metric pitch)	8672	tires, foam inserts) (2) (TSM rated) Tires & wheels, assembled, glued (black wheels, Talon EXT tires,
448R 449	Spur gear, 50-tooth, steel (wide-face, 1.0 metric pitch) Spur gear, 54-tooth (1.0 metric pitch)		foam inserts) (2) (17mm splined) (TSM rated)
449R	Spur gear, 54-tooth, steel (wide-face, 1.0 metric pitch)	8672G	Tires & wheels, assembled, glued (green wheels, Talon EXT tires, foam inserts) (2) (17mm splined) (TSM rated)
2704	Steering Components	8672A	Tires & wheels, assembled, glued (orange wheels, Talon EXT tires, foam inserts) (2) (17mm splined) (TSM rated)
)72A	Gear set (for 2070, 2075 servos)	4983A	Tires & wheels, assembled, glued (SS (Split Spoke) black
072R 355X	Gear set, metal, high speed (for 2070, 2075 servos) Hollow ball set, aluminum (30)/ tall centered hollow ball (2)/ tall		chrome wheels, Maxx® tires (6.3" outer diameter), foam insert
	offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2)		(2) (use with 17mm splined wheel hubs & nuts, part #5353X) (I Revo®/T-Maxx®/E-Maxx) (TSM rated)
355	Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2)	5670 4973	Tires, Canyon AT 3.8" (2)/ foam inserts (2) Tires, Maxx® 3.8" (6.3" outer diameter (160mm)) (2) (fits
343X	Mount, steering arm/ steering stops (2) (lower hinge pin retainer)		Revo®/T-Maxx®/E-Maxx)
100	(includes standard and maximum throw steering stops)	5171 8673	Tires, Maxx® Chevron 3.8" (2) (fits Revo®/T-Maxx®/E-Maxx) Tires, paddle 3.8" (2)/ foam inserts (2)
469 646	Rod ends (GTR shocks) (6) Rod ends, heavy duty (toe links) (8) (assembled with hollow balls)	5375	Tires, Response Pro 3.8" (soft-compound, narrow profile, sho
349	Rod ends, small, with hollow balls (6) (for Rev o® steering linkage)		knobby design)/ foam inserts (2)
345X	Servo horns, steering and throttle (for non-Traxxas® servos (Hitec, JR, KO, Airtronics))	5471	Tires, Response racing 3.8" (soft-compound, narrow profile, short knobby design)/ foam inserts (2)
345R	Serv o horns, steering, long (2), short (2)/ linkage, steering (3x20mm turnbuckle) (2)/ rod ends (short) (4)/ hollow balls (4)	5470	Tires, SportTraxx racing 3.8" (soft compound, directional and asymmetrical tread design)/ foam inserts (2)
344X	Servo saver spring, heavy duty (for use with metal-gear servos)	8670	Tires, Talon EXT 3.8" (2)/ foam inserts (2)
075R 075	Servo, digital high-speed, metal gear (ball bearing), waterproof Servo, digital high-torque (ball bearing), waterproof	8654	Wheel hubs, splined, 17mm (blue-anodized) (4)/ 4x5 GS (4)/ 3x14i pin (4)
)75X	Servo, digital high-torque, metal gear (ball bearing), waterproof	8654G	Wheel hubs, splined, 17mm (green-anodized) (4)/ 4x5 GS (4)/ 3x14mm pin (4)
344	Steering arm (upper & lower)/ servosaver/servosaver spring/ steering arm shaft	8654A	Wheel hubs, splined, 17mm (orange-anodized) (4)/ 4x5 GS (4)/
638	Toe link, 5.0mm steel (front or rear) (2)	8654R	3x14mm pin (4) Wheel hubs, splined, 17mm (red-anodized) (4)/ 4x5 GS (4)/
638X	Toe links, E-Revo® VXL (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends,		3x14mm pin (4)
	assembled with steel hollow balls (8)/ aluminum wrench, 10mm	7758A 7758	Wheel nuts, splined, 17mm, serrated (black-anodized) (4) Wheel nuts, splined, 17mm, serrated (blue-anodized) (4)
	(1)	7758G	Wheel nuts, splined, 17mm, serrated (green-anodized) (4)
38G	Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends,	7758T	Wheel nuts, splined, 17mm, serrated (orange-anodized) (4)
	assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1)	7758R 8671	Wheel nuts, splined, 17mm, serrated (red-anodized) (4) Wheels, 3.8" (black) (2) (17mm splined)
338R	Toe links, E-Revo® VXL (TUBES red-anodized, 7075-T6	8671G	Wheels, 3.8" (green) (2) (17mm splined)
	aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm	8671A	Wheels, 3.8" (orange) (2) (17mm splined) Transmission Components
	(1)	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
	Suspension Linkage	8681X	Carrier, differential (aluminum)/ x-ring gaskets (2)/ ring gear gaske
355X	Hollow ball set, aluminum (30)/ tall centered hollow ball (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2)	8677	spacers (4)/ 12.2x18x0.5 metal washer Cov er, gear/ 3x12mm CS (1)
355	Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer	6465	Cush driv e key / pin/ elastomer damper
240	adjustment shims; 3.5mm (2), 1.17mm (2)	8682	Gear set, differential (spider gears (4), spider gear shaft (2))
619 619X	Push rods (steel), heavy duty (2) (assembled with rod ends)	8691	Gearbox halves (front & rear)/ idler gear shaft
DISK	Push rods, aluminum (blue-anodized), heavy duty (2) (assembled with rod ends and threaded inserts)	5041 7793X	Grease, premium high performance (20cc) Housing, cush drive (front & rear halves)
619G	Push rods, aluminum (green-anodized), heavy duty (2)	8692	Input shaft/ idler gear
619R	(assembled with rod ends and threaded inserts) Push rods, aluminum (red-anodized), heavy duty (2) (assembled	8661	Motor mount hinge post/fixed gear adapter/ 5x25mm BCS (1)/ 4x16mm CS with split and flat washer (1)
	with rod ends and threaded inserts)	5660	Motor mount, finned aluminum
469 247×	Rod ends (GTR shocks) (6)	8685	Output gear, 36-tooth, metal
647X	Rod ends, heavy duty (push rod) (8) (assembled with hollow balls) (replacement ends for #8619, 8619G, 8619R, 8619X)	8684	Output gear, center differential, hardened steel (2)
646	Rod ends, heavy duty (toe links) (8) (assembled with hollow balls)	8690 3965	Plate, motor Screws, 2.5x8mm cap-head machine (6)
345R	Serv o horns, steering, long (2), short (2)/ linkage, steering (3x20mm	2552	Screws, 3x12mm countersunk machine (6) (hex drive)
321	turnbuckle) (2)/ rod ends (short) (4)/ hollow balls (4) Suspension pin set (front or rear, hardened steel), 3x20mm (4),	1647 8695	Silicone grease Transmission, complete (fits E-Revo® VXL)
638	3x40mm (2)) Too link 5.0mm steel (front or rear) (2)		Traxxas Tools
იაი 638X	Toe link, 5.0mm steel (front or rear) (2) Toe links, E-Revo® VXL (TUBES blue-anodized, 7075-T6	3433X	Body reamer (aluminum handle)
	aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm	3433	Body reamer (plastic handle)
	accomplete with close monow build to, aluminum wienen, itilim	3436 3432	Cap, body reamer
	(1)	3432	Scissors, curved tip
638G	(1) Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6	3431	Scissors, straight tip
638G		3431 8712	
	Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1)		Scissors, straight tip Speed Bit Essentials Set, hex and nut driver, 7-piece, include: premium handle (medium), travel pouch, hex drivers (straight 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mn
	Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1) Toe links, E-Revo® VXL (TUBES red-anodized, 7075-T6		Speed Bit Essentials Set, hex and nut driver, 7-piece, include premium handle (medium), travel pouch, hex drivers (straight
	Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1) Toe links, E-Revo® VXL (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends,	8712 8721	Speed Bit Essentials Set, hex and nut driver, 7-piece, include premium handle (medium), travel pouch, hex drivers (straight 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm and 8.0mm), 1/4" drive Speed bit handle, medium (one piece)
	Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1) Toe links, E-Revo® VXL (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1)	8712 8721 8720	Speed Bit Essentials Set, hex and nut driver, 7-piece, include premium handle (medium), travel pouch, hex drivers (straight 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm and 8.0mm), 1/4" drive Speed bit handle, medium (one piece) Speed bit handle, premium, large (rubber overmold)
	Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1) Toe links, E-Revo® VXL (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1)	8712 8721 8720 8722	Speed Bit Essentials Set, hex and nut driver, 7-piece, include premium handle (medium), travel pouch, hex drivers (straight 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm and 8.0mm), 1/4" drive Speed bit handle, medium (one piece) Speed bit handle, premium, large (rubber overmold) Speed bit handle, premium, medium (rubber overmold)
638R	Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1) Toe links, E-Revo® VXL (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1)	8712 8721 8720	Speed Bit Essentials Set, hex and nut driver, 7-piece, include premium handle (medium), travel pouch, hex drivers (straight 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm and 8.0mm), 1/4" drive Speed bit handle, medium (one piece) Speed bit handle, premium, large (rubber overmold) Speed bit handle, premium, medium (rubber overmold) Speed Bit Master Set, hex and nut driver, 13-piece, includes
638G 638R 514 160X	Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1) Toe links, E-Revo® VXL (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm (1)	8712 8721 8720 8722	Speed Bit Essentials Set, hex and nut driver, 7-piece, included premium handle (medium), travel pouch, hex drivers (straight 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm and 8.0mm), 1/4" drive Speed bit handle, medium (one piece) Speed bit handle, premium, large (rubber overmold) Speed bit handle, premium, medium (rubber overmold)

Page 5 E-Revo® VXL Brushless: TQi™ Traxxas Link™ Enabled 2.4GHz Radio & TSM® (Model 86086-4) Parts List

8719 Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive 8716 Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive 8716X Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm), 1/4" drive 8715 Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive 8715X Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive 8715X Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive 3415 Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/#00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/driver handle ###################################	8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive
drive 8716X Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm), 1/4" drive 8715 Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive 8715X Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive 3415 Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/driver handle 11111111111111111111111111111111111	8719	handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm,
3.0mm), 1/4" drive 8715 Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive 8715X Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive 3415 Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle 11111111111111111111111111111111111	8716	• • • • • • • • • • • • • • • • • • • •
2.5mm), 1/4" drive 8715X Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive 3415 Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle TUTTINICKIES & TINGRIGI ROIS 5477 Flat wrench, 5mm (blue-anodized aluminum) Linkage, steering (Rev o® 3.3) (3x50mm Turnbuckle) (2)/ rod ends (short) (4)/ hollow balls (4)	8716X	
2.5mm, 3.0mm), 1/4" drive Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle Tilliance (See Tilliance) Flat wrench, 5mm (blue-anodized aluminum) Linkage, steering (Revo® 3.3) (3x50mm Turnbuckle) (2)/ rod ends (short) (4)/ hollow balls (4)	8715	
3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/ driver handle TUITIBUCKIES & TINGAUGI ROIS 5477 Flat wrench, 5mm (blue-anodized aluminum) Linkage, steering (Rev o® 3.3) (3x50mm Turnbuckle) (2)/ rod ends (short) (4)/ hollow balls (4)	8715X	
5477 Flat wrench, 5mm (blue-anodized aluminum) 5341 Linkage, steering (Rev o® 3.3) (3x50mm Turnbuckle) (2)/ rod ends (short) (4)/ hollow balls (4)	3415	3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/
5341 Linkage, steering (Revo® 3.3) (3x50mm Turnbuckle) (2)/ rod ends (short) (4)/ hollow balls (4)		Turnbuckles & Threaded Rods
(short) (4)/ hollow balls (4)	5477	Flat wrench, 5mm (blue-anodized aluminum)
Push rods (steel), heavy duty (2) (assembled with rod ends)	5341	
	8619	Push rods (steel), heavy duty (2) (assembled with rod ends)
8619X Push rods, aluminum (blue-anodized), heavy duty (2) (assembled with rod ends and threaded inserts)	8619X	Push rods, aluminum (blue-anodized), heavy duty (2) (assembled with rod ends and threaded inserts)
8619G Push rods, aluminum (green-anodized), heavy duty (2)	8619G	· · · · · · · · · · · · · · · · · · ·

(assembled with rod ends and threaded inserts)

8619R Push rods, aluminum (red-anodized), heavy duty (2) (assembled with rod and sand threaded inserts)

with rod ends and threaded inserts)

8647X Rod ends, heavy duty (push rod) (8) (assembled with hollow balls)

(replacement ends for #8619, 8619G, 8619R, 8619X)

8646 Rod ends, heavy duty (toe links) (8) (assembled with hollow balls)

8638 Toe link, 5.0mm steel (front or rear) (2)

8638X Toe links, E-Revo® VXL (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm

Toe links, E-Revo® VXL (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (144mm) (2)/ rod ends, assembled with steel hollow balls (8)/ aluminum wrench, 10mm

(1)
Toe links, E-Revo® VXL (TUBES red-anodized, 7075-T6
aluminum, stronger than titanium) (144mm) (2)/ rod ends,
assembled with steel hollow balls (8)/ aluminum wrench, 10mm

(1)

8638G

8638R

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM