
ISDT P20 Dual Smart Charger 1-8S 500W (x2) 20A (2x) 800W/35A parallel Ladegerät

Art.Nr.: ISDT-P20

ISDT P20 Dual Smart Charger 1-8S 500W (x2) 20A (2x) 800W/35A parallel
Ladegerät

Features:

- Ladestrom/Ausgang: 0,2-20A
- Eingangsspannung: 10-34
- Länge: 105mm
- Entladeleistung je Ausgang: 15W
- NiCd/NiMH Akkus: 1-16
- Ladestrom: bis 20A
- Bleibatterien: bis 24V
- Leistung: 2x 500W / 800W Parallel
- Max. Entladeleistung: 30W
- LiHv Zellen: bis 7
- LiPo Zellen: bis 8
- Stecker Typ Eingang: XT60i
- Stecker Typ Ladeausgang: XT60i
- Stecker Typ Balancer: XH

Technische Daten

Eingangsspannung (V):	10-34
ladbare Akkutypen:	LiPo/LiFe/Lilon/LiHV/NiMH/NiCd/Pb
ladbare Zellenzahl:	1-8 Lixx, 1-7 LiHV, 1-16 Nixx, 1-12 Pb
Ladestrom (A):	0,2-20
Entladestrom (A):	0,2-1,5
Ladegeräte (Kategorie):	DC 12-50V
Leistung/Watt (W):	500 x2
Ladestrom (Kategorie):	Bis 20A
Entladestrom (Kategorie):	Bis 5A

Auswahl-Kategorie:

Ladegeräte 12V



PREIS:

129,99 EUR

inkl. 19 % MwSt. zzgl. **Versandkosten**

High Power Synchronous Dual Channel, with Smart Charging.

Smart High-Speed Processor. Adaptive power transfer interface to each port. Supports PPS with Maximum charging power up to 200W / PPS / 500W PPS for single port. Charge ICET. Powered by Innovation.



P10 **P20**

ES ES

TDA × 1 ZDA × 2

500W × 1 800W PARALLEL CHARGING POWER



Signature original creative interactive systems

Over 152 countries and regions, Support on-line upgrading for more language, and higher interactive system for global market.

繁体中文	Español
繁體中文	italiano
English	русский
Deutsch	한국어
Français	العربية
हिन्दी	Portugul
日本語	עברית



Support USB interface to upgrade firmware

Connecting the computer through the USB-C interface, upgrade to the latest firmware. Always maintain the advanced performance and features.



Adjustable Digital Power Supply

The DMI of the charger can receive a DC power supply. It is suitable for power supply mode. The Max power is 100W / PPS / 500W PPS. DC 0.5-5.0V / 1.0-5.0A. DC 0.5-5.0V / 1.0-5.0A.

