Futaba DLPH-1 Akku Weiche Dual-Link, S-Bus Decoder, Dual Battery Power Distribution System

Art.Nr.: P-DLPH-1

Mit dem Futaba Dual Link Power Hub DLPH-1 vervierfachen Sie die Sicherheit in Ihrem Modell, indem zwei S.BUS/S

Der Futaba DLPH-1 ist ausgelegt f?r die Hochstromversorgung von Futaba S.BUS Empf?ngern und normalen Servo

M?ssen gleichzeitig mehrere Servos mit viel Kraft und/oder hoher Geschwindigkeit arbeiten, stellt dies grunds?tzli

Der Futaba DLPH-1 l?st daher folgende Probleme:

• Die Servos mit hohem Strombedarf werden am DLPH-1 angeschlossen, nicht mehr am Empf?nger.

• Der DLPH-1 besitzt durch die eingebaute Akkuweiche zwei XT60 Hochstromanschl?sse f?r zwei Empf?ngerakkus

• Das Positions- und Stellsignal f?r die Servos wird separat vom Empf?nger an die einzelnen Steckanschl?sse gele

• Das Stell- und Positionssignal wird ?ber den S.BUS zu den Steckanschl?ssen des DLPH-1 geleitet.

• Der Betriebsstrom f?r Servos und Empf?nger wird also „aufgesplittet“.

Technische Daten

Servoausg?nge: 18 S.BUS Aus-/Eing?nge: 2 Akkuanschluss: 2x XT60 Passende Akkus: LiFe 2s, LiPo 2s, LiPo 3s (NIC

Features

Hochstromversorgung von Empf?nger und Servos Integrierte Empf?nger- & Akkuweiche 2x S.BUS Empf?ngeransch

---

Lieferumfang

DLPH-1 Futaba Dual Link Power Hub Schalterkabel 2x Patchkabel f?r Empf?nger Mini-Schraubendreher Befestigun

---

Futaba DLPH-1 - Link Unit for Dual Receivers and Dual Batteries + S.Bus Decoder

Dual Receiver System

For extra security, the DLPH-1 unit automatically switches to the second

sub receiver if there is an issue with the main receiver. Then it automatically switches back to the main receiver when communication is recovered.

Dual Battery System

Two power supply batteries can be connected to the DLPH-1. Power is supplied from the battery with the highest voltage. The operating time is the total time of the 2 batteries. For example, even if the voltage of one battery drops, power can be supplied from the other battery. Even one battery can be used, but safer flight is possible if 2 batteries are used.

Use batteries with sufficient capacity for the specifications and number of servo motors to be used.

Specs:

- S.BUS/S.BUS2
- Use: Two receivers and two batteries communication switching device
- Size: 62.8?62.4?18.1mm
- Weight: 50g
- FET rated: Always 60A / 2pcs
- Operating Voltage: DC6.4 to 13.0V
- Receiver Batteries (dual): 2S LiFe or 2-3S LiPo with XT60 connectors
- Accessories: Switch / Receiver connection cord x 2 / Mini screwdriver/ Flange damper / Eyelet / Wood screw

PREIS:

Unser bisheriger Preis ~~229,00 EUR~~

Jetzt nur 159,00 EUR

Sie sparen 31 % /70,00 EUR

inkl. 19 % MwSt. zzgl. Versandkosten